

## MDF Primer

Specifically formulated for use on interior and exterior medium density fibre board. It offers a low odour alternative to traditional solvent based primers producing an ideal surface for over coating with a subsequent top coat and its quick drying properties enable two or three coats to be applied in just one day.

### Recommended uses

Interior ✓ Exterior ✗

### Type of substrate

Interior and exterior medium density fibre board. For further information on substrates please contact Technical Advisory

### Colour availability

White (2.5ltr & 750ml)

### Finish

Matt

### Volume solid

36%

### Coverage

1 litre will cover approximately 13 square metres per litre, depending on the nature and porosity of the surface.

### Drying time

Touch dry in 30 minutes

Recoat in 1-2 hours

### Transportation and storage

PROTECT FROM FROST.

To avoid the risk of spillage, always store and transport in a secure upright position.

Lift with care - gross weight does not exceed 4 kilograms. (2.5L).

### Film thickness

Wet: 77 micron

Dry: 27 micron

### Preparation

Ensure that the surface to be painted is clean, dry and free from loose and flaking material. Nail heads should be treated with Leyland Anti-Corrosive Metal Primer. Rub down previously painted surfaces with fine waterproof abrasive paper to provide a key and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory on

### Application

Stir well before use. Apply by a brush or roller which should be clean and free from solvent and oil. Apply liberally, brushing firmly into the surface. Do not apply when the air or surface temperature is below 10°C or externally when rain is imminent. A second coat serves as an excellent undercoat for gloss finishes. Under normal conditions, touch dry in 30 minutes, recoatable after 1-2 hours. High humidity can retard the drying time.

### Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use in warm soapy water and rinse thoroughly. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

### Warning

- Keep out of reach of children.
- Avoid contact with skin and eyes.
- Do not ingest.
- If medical advice is needed have container or label to hand.
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency.