

Alkali Resisting Wall Primer

A solvent-based alkali-resisting primer and sealer for interior and exterior masonry surfaces. Resists alkali attack and promotes first class adhesion. Also suitable for use on other surfaces including wood and fibreglass. Ideal for use under both oil-based and water-borne paints.

Recommended uses

Interior ✓ Exterior ✓

Type of substrate

Plaster, concrete, cement rendering, brick, stone and blockwork.

Colour availability

White (5ltr & 2.5ltr)

Finish

N/A

Volume solid

57%

Coverage

1 litre will cover approximately 10 square metres depending on the nature and porosity of the surface.

Drying time

Touch dry in 4-6 hours.
Recoat after 16-24 hours.

Transportation and storage

To avoid the risk of spillage, always store and transport in a secure upright position. Store away from heat and flame.

VOC content

HIGH VOC CONTENT 25-50%
VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/g): 350 g/l (2010). This product contains max 350 g/l VOC.

Film thickness

Wet: 50µm
Dry: 28µm

Preparation

Ensure surface to be painted is sound, clean, dry and free from grease. Rub down the bare timber surfaces with dry glasspaper to remove raised grain and sharp edges. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Apply Knotting Solution to knots and resinous areas, and allow to dry thoroughly. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory.

Application

Stir well before use. Suitable for application by brush or roller. Apply liberally, working firmly into the surface and laying off in the line of the grain. Take care to treat all accessible timber particularly the end grain. Allow to dry thoroughly before applying the relevant undercoat and finishing paint.

Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for disposal of waste coatings. Do not empty product into drains or watercourses. Replace lid firmly.

Warning

- Flammable liquid and vapour.
- Contains 2-butanone oxime. May produce an allergic reaction.
- Safety data sheet available on request.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Repeated exposure may cause skin dryness or cracking.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Do not get in eyes, on skin, or on clothing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.
- Ensure maximum ventilation during application and drying.
- Not recommended for interior use on large surface areas, or in confined spaces.
- Store in a well-ventilated place. Keep cool.
- Keep container tightly closed.

