

Stain Blocking Primer

Specifically formulated to seal in unsightly stains caused by nicotine, smoke, marker pen, wax crayon, graffiti, tannin and bitumen. It provides a tough durable matt coating which prevents stains bleeding through from the substrate. Once dry over coat with any of Leyland's water based emulsions.

Recommended uses

Interior ✓

Type of substrate

Plywood, Brick, Concrete, Cedar & Redwood. For further information on substrates please contact Technical Advisory on 01924 354354.

Colour availability

White (2.5ltr)

Finish

Matt

Volume solid

42%

Coverage

1 litre will cover approximately 8 square metres depending on the nature and porosity of the surface.

Drying time

Recoat after 2 hours

Transportation and storage

STORE AWAY FROM HEAT AND FLAME.

To avoid the risk of spillage, always store and transport in a secure upright position.

Lift with care - gross weight does not exceed 4 kilograms.

Film thickness

Wet: 125 micron

Dry: 53 micron

Preparation

All surfaces should be clean, dry and free from grease. Remove any crazed or flaking paint. Rub down with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre 1960s paint surfaces over wood and metal as they may contain harmful lead. For further assistance contact Technical Advisory on 01924 354354. Please note this product will not prevent stains caused by water damage unless the fault has been eradicated, and the substrate allowed to dry.

Application

Stir well before use. Apply by brush or roller, covering the stain and a surrounding area of 20cm to ensure maximum containment. Heavily soiled areas may require additional coats. Allow 2-4 hours under normal conditions between coats.

Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with White Spirit or Brush Cleaner. Replace lid firmly after use. Some local authorities have special facilities for disposal of waste coatings. Do not empty product into drains or watercourses.

Warning

- Keep out of reach of children.
- Avoid contact with skin and eyes.
- Do not ingest.
- If medical advice is needed have container or label to hand.
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency.