

## Truguard Pliolite<sup>®</sup> Based Masonry

Specially formulated on durable Pliolite<sup>®</sup> Resin, providing excellent adhesion to the substrate, eliminating the need for a separate stabilising primer and providing resistance to rain within 20 minutes of application. The smooth, durable, matt finish can be applied in temperatures as low as -5 °C, enabling year-round application.



The British Board of Agrément is designated by Government to issue European Technical Approvals based on the assessment of products for construction. Leyland's products carrying this logo have undergone rigorous independent testing and received approval from the BBA.

### Recommended uses

Interior **X** Exterior **✓**

### Type of substrate

Softwood, hardwood and plywood panels. Also suitable for use on metal.

### Colour availability

Brilliant White and a range of ready mixed colours (5ltr). Thousands of tinted colours also available (5ltr)

### Finish

Matt

### Volume solid

49%

### Coverage

1 litre will cover approximately 8 square metres on smooth surfaces. In common with all wall paints, the spreading rate will be reduced on rough and absorbent surfaces such as pebble dash. When using more than one tin of a colour, it is advised that you intermix the quantity required beforehand.

### Drying time

Recoat after 24 hours.

### Transportation and storage

To avoid the risk of spillage, always store and transport in a secure upright position. Store away from heat and flame.

### Film thickness

Wet: 125µm

Dry: 61µm

### Preparation

Ensure surface to be painted is sound, clean, dry and free from grease. Treat any mould or lichen with Sterilisation Wash as directed. Chalky, underbound surfaces should be scraped, dry brushed and sealed with Leyland Truguard Stabilising Masonry Primer. Wear a suitable face mask if creating dust.

### Application

Stir well before use. Do not thin. Apply two coats, allowing 16-24 hours between coats under normal conditions. Do not apply to surfaces which are to be overcoated with conventional undercoat and gloss paint. Suitable for application by brush, roller, conventional or airless spray.

### Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with white spirit. Some local authorities have special facilities for disposal of waste coatings. Do not empty product into drains or watercourses. Replace lid firmly.

### Warning

- Keep out of reach of children.
- Avoid contact with skin and eyes.
- Do not ingest.
- Do not breathe spray. Wear respiratory protection.
- If medical advice is needed have container or label to hand.
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency.